

MAGELLAN™ ADD ON OPTIONS

Programming codes are for the following products:

- Magellan™ 800i
- Magellan™ 1000i
- Magellan™ 1100i
- Magellan™ 1400i
- Magellan™ 2200
- Magellan™ 2200E
- Magellan™ 2300
- Magellan™ 2300E
- Magellan™ 3200
- Magellan™ 3300
- Magellan™ 8100
- Magellan™ 8200
- Magellan™ 8300
- Magellan™ 8400
- Magellan™ 8500
- Magellan™ 8500XT
- Magellan™ 8500XTS
- Magellan™ 9500

How to Program Conditional Add-ons

- (1). Scan the Switch Label on the following page to enter the scanner into programming mode.
- (2). Scan one of the Conditions (Condition 1-4) barcodes on the following page.
- (3). Scan the number barcode that corresponds to the first flag in the barcode you want to perform the condition on.

Example: 2834500574499 12355

If value does not matter, scan the Don't Care barcode. Note: Scanning A, B, or C in this instance can produce unpredictable results.

- (4). Scan the number barcode that corresponds to the second flag in the barcode you want to perform the condition on.

Example: 2834500574499 12355

If value does not matter, scan the Don't Care barcode. Note: Scanning A, B, or C in this instance can produce unpredictable results.



(5). Scan the number barcode that corresponds to the third flag in the barcode you want to perform the condition on.
Example: 2834500574499 12355

If value does not matter, scan the Don't Care barcode. Note: Scanning A, B, or C in this instance can produce unpredictable results.

(6). Scan the alphanumeric barcode that corresponds to the type of add-on you wish to set for this condition.

1 = UPCA + P2

2 = UPCA + P5

3 = UPCA + P8

4 = UPCE + P2

5 = UPCE + P5

6 = UPCE + P8

7 = EAN13 + P2

8 = EAN13 + P5

9 = EAN13 + P8


A = EAN8 + P2

B = EAN8 + P5


C = EAN8 + P8




Switch



Condition 1



Condition 2
















Condition 3




Condition 4






Optional Add-ons

Enable Optional P2




Disable Optional P2




Enable Optional P5




Disable Optional P5



Enable Optional P8



Disable Optional P8



Timer for Optional Add-ons

This setting is the amount of time the scanner will look for an optional add-on when scanning a barcode.

(1). Scan the Switch Label to enter programming mode.



(2). Scan the Timer Optional Add-ons followed by a value of 01-10 (1 = 10ms) using the number barcodes on page 4.




(3). Scan the Switch Label to end programming.





Minimum Read Setting for P2 and P5 Add-ons

This sets the minimum times a P2 or P5 add-on must be read before the scanner sees it as valid.

(1). Scan the Switch Label to enter programming mode.



(2). Scan the P2 or P5 followed by a value of 01-15 using the number barcodes on page 4.



(3). Scan the Switch Label to end programming

