

## RS-232 PARAMETER OPTIONS

Programming codes are for the following products:

- Gryphon™ GD4100
- Gryphon™ GM4100
- Gryphon™ GBT4100
- Gryphon™ GD4300
- Quickscan™ QD2100
- Quickscan™ QW2100
- PowerScan™ PD7100
- PowerScan™ PBT7100
- Touch™ TD1100

### Baud Rate Options

Baud Rate = 1200



Baud Rate = 2400



Baud Rate = 4800



Baud Rate = 9600



Baud Rate = 19200



Baud Rate = 38400



<sup>3</sup> \$ P , C R 2 B A 0 5 , P

Baud Rate = 57600



<sup>3</sup> \$ P , C R 2 B A 0 6 , P

Baud Rate = 115200



<sup>3</sup> \$ P , C R 2 B A 0 7 , P

## Data Bit Options

Data Bits = 7



<sup>3</sup> \$ P , C R 2 D A 0 0 , P

Data Bits = 8



<sup>3</sup> \$ P , C R 2 D A 0 1 , P

## Stop Bit Options

Stop Bits = 1



<sup>3</sup> \$ P , C R 2 S T 0 0 , P

Stop Bits = 2



<sup>3</sup> \$ P , C R 2 S T 0 1 , P

